


2908214

https://www.phoenixcontact.com/ae/products/2908214

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.





Commercial data

Item number	2908214
Packing unit	10 pc
Minimum order quantity	10 pc
Sales key	DKF
Product key	DKF313
GTIN	4055626289144
Weight per piece (including packing)	55.07 g
Weight per piece (excluding packing)	50.5 g
Customs tariff number	85366990
Country of origin	CN



2908214

https://www.phoenixcontact.com/ae/products/2908214

Technical data

Product properties

Product type	Relay socket
Product family	ESSENTIAL edition

Electrical properties

Nominal voltage U _N	250 V AC/DC
Nominal current I _N	5 A

Connection data

Input side

Connection method	Bolt connection
Stripping length	8 mm
Screw thread	M3
Conductor cross-section rigid	2x 0.2 mm ² 2.5 mm ² (without ferrule)
	2x 0.2 mm ² 1.5 mm ² (with ferrule)
Conductor cross-section flexible	2x 0.2 mm ² 2.5 mm ² (without ferrule)
	2x 0.2 mm ² 1.5 mm ² (with ferrule)

Output side

Connection method	Bolt connection
Stripping length	8 mm
Screw thread	M3
Conductor cross-section rigid	2x 0.2 mm ² 2.5 mm ² (without ferrule)
	2x 0.2 mm ² 1.5 mm ² (with ferrule)
Conductor cross-section flexible	2x 0.2 mm ² 2.5 mm ² (without ferrule)
	2x 0.2 mm ² 1.5 mm ² (with ferrule)

Dimensions

Width	29.8 mm
Height	64.9 mm
Depth Retaining bracket	63 mm (ECOR-RHM-2)

Material specifications

Environmental and real-life conditions

Ambient conditions

Ambient temperature (operation)	-25 °C 55 °C
Ambient temperature (storage/transport)	-25 °C 55 °C

Mounting



2908214

https://www.phoenixcontact.com/ae/products/2908214

Mounting type	DIN rail mounting
Mounting position	any



2908214

https://www.phoenixcontact.com/ae/products/2908214

Approvals

🌣 To download certificates, visit the product detail page: https://www.phoenixcontact.com/ae/products/2908214



cUL Recognized

Approval ID: FILE E 113228



UL Recognized

Approval ID: FILE E 113228



EAC

Approval ID: RU C-DE.**08.B.01419



cULus Recognized

Approval ID: E113228



2908214

https://www.phoenixcontact.com/ae/products/2908214

Classifications

ECLASS

	ECLASS-13.0	27371603
	ECLASS-15.0	27371603
ETIM		
	ETIM 9.0	EC001456
UNSPSC		
	UNSPSC 21.0	39122300



2908214

https://www.phoenixcontact.com/ae/products/2908214

Environmental product compliance

Fulfills EU RoHS substance requirements	Yes, No exemptions	
China RoHS		
Environment friendly use period (EFUP)	EFUP-E	
	No hazardous substances above the limits	
EU REACH SVHC		
REACH candidate substance (CAS No.)	No substance above 0.1 wt%	
EF3.0 Climate Change		
CO2e kg	1.018 kg CO2e	



2908214

https://www.phoenixcontact.com/ae/products/2908214

Mandatory accessories

REL-IR-BL/L- 12DC/4X21 - Single relay

1109557

https://www.phoenixcontact.com/ae/products/1109557



Plug-in industrial relay in basic design with power contacts, 4 changeover contacts, test button, status LED, mechanical switch position indicator, polarity A1+, A2-, input voltage: 12 V DC

REL-IR-BL- 24DC/4X21 - Single relay

1032521

https://www.phoenixcontact.com/ae/products/1032521



Plug-in industrial relay in basic design with power contacts, 4 changeover contacts, test key, mechanical switch position indicator, polarity A1+, A2-, input voltage: $24\ V\ DC$



2908214

https://www.phoenixcontact.com/ae/products/2908214

REL-IR-BL/L- 24DC/4X21 - Single relay

1032527

https://www.phoenixcontact.com/ae/products/1032527



Plug-in industrial relay with power contacts, 4 changeover contacts, test button, status LED, mechanical switch position indicator, input voltage: 24 V DC $\,$

REL-IR-BL/L- 48DC/4X21 - Single relay

1109558

https://www.phoenixcontact.com/ae/products/1109558



Plug-in industrial relay in basic design with power contacts, 4 changeover contacts, test button, status LED, mechanical switch position indicator, polarity A1+, A2-, input voltage: 48 V DC



2908214

https://www.phoenixcontact.com/ae/products/2908214

REL-IR-BL/L-110DC/4X21 - Single relay

1109560

https://www.phoenixcontact.com/ae/products/1109560



Plug-in industrial relay in basic design with power contacts, 4 changeover contacts, test button, status LED, mechanical switch position indicator, polarity A1+, A2-, input voltage: 110 V DC

REL-IR-BL/L-125DC/4X21 - Single relay

1109561

https://www.phoenixcontact.com/ae/products/1109561



Plug-in industrial relay in basic design with power contacts, 4 changeover contacts, test button, status LED, mechanical switch position indicator, polarity A1+, A2-, input voltage: 125 V DC



2908214

https://www.phoenixcontact.com/ae/products/2908214

REL-IR-BL/L-220DC/4X21 - Single relay

1109562

https://www.phoenixcontact.com/ae/products/1109562



Plug-in industrial relay in basic design with power contacts, 4 changeover contacts, test button, status LED, mechanical switch position indicator, polarity A1+, A2-, input voltage: 220 V DC

REL-IR-BL/L- 24AC/4X21 - Single relay

1109563

https://www.phoenixcontact.com/ae/products/1109563



Plug-in industrial relay in basic design with power contacts, 4 changeover contacts, test button, status LED, mechanical switch position indicator, input voltage: 24 V AC



2908214

https://www.phoenixcontact.com/ae/products/2908214

REL-IR-BL/L-115AC/4X21 - Single relay

1109564

https://www.phoenixcontact.com/ae/products/1109564



Plug-in industrial relay in basic design with power contacts, 4 changeover contacts, test button, status LED, mechanical switch position indicator, input voltage: 115 V AC

REL-IR-BL-230AC/4X21 - Single relay

1032529

https://www.phoenixcontact.com/ae/products/1032529



Plug-in industrial relay in basic design with power contacts, 4 changeover contacts, test key, mechanical switch position indicator, input voltage: 230 V AC



2908214

https://www.phoenixcontact.com/ae/products/2908214

REL-IR-BL/L-230AC/4X21 - Single relay

1032531

https://www.phoenixcontact.com/ae/products/1032531



Plug-in industrial relay with power contacts, 4 changeover contacts, test button, status LED, mechanical switch position indicator, input voltage: 230 V AC

Accessories

DB 50-90 BU - Wire bridge

2821180

https://www.phoenixcontact.com/ae/products/2821180

Flexible wire loop bridge, 50-pos., conductor cross-section: 0.5 mm², loop length: 90 mm, ferrule length: 8 mm, color: blue





2908214

https://www.phoenixcontact.com/ae/products/2908214

DB 50-90 BK - Wire bridge

2820916

https://www.phoenixcontact.com/ae/products/2820916

Flexible wire loop bridge, 50-pos., conductor cross-section: 0.5 mm², loop length: 90 mm, ferrule length: 8 mm, color: black



DB 50-90 GY - Wire bridge

2820929

https://www.phoenixcontact.com/ae/products/2820929

Flexible wire loop bridge, 50-pos., conductor cross-section: 0.5 mm², loop length: 90 mm, ferrule length: 8 mm, color: gray





2908214

https://www.phoenixcontact.com/ae/products/2908214

ECOR-RHM-2L - Relay retaining bracket

1047026

https://www.phoenixcontact.com/ae/products/1047026



Relay retaining bracket, wire model, suitable for ECOR-2... relay base when used with REL-IR-BL... relays

Phoenix Contact 2025 @ - all rights reserved https://www.phoenixcontact.com

PHOENIX CONTACT Middle East FZ LLC 1201N-1206N, Dubai Science Park Towers – North P.O. Box 345002, Dubai, United Arab Emirates (+971) 4 437-0324 info-me@phoenixcontact.com